



# S-1068

## Water and Oil repellent for resins Technical Information

### 1. Features

- S-1068 is an acrylic copolymer that includes perfluorinated units.
- S-1068 provides surface repellency when mixed with resin at low dosages.
- S-1068 offers increased performance when mixed with resins of different crystallinity (for example, Polyethylene & Polypropylene).

### 2. Typical Properties

Appearance..... White powder  
Percent volatile .....< 2 mass %  
Melting point .....104°F (40°C)

### 3. Shipping & Storage

Non-Red Label (Non-flammable Material)

S-1068 should be stored at temperatures between 23°F and 70°F (-5°C and 21°C)

### 4. Safety / Toxicology

Before using this product, please read the current S-1068 Material Safety Data Sheet and the precautionary statement on the product package. Follow all applicable directions.

DAIKIN AMERICA, INC.

ADDRESS: 20 Olympic Drive, Orangeburg, New York 10962

EMERGENCY PHONE: 1-256-306-5000

PRODUCT INFORMATION: 1-800-365-9570

DAIKIN INDUSTRIES, LTD.

CHEMICAL DIVISION

ADDRESS: Umeda Center Bldg.,4-12, Nakazaki-Nishi 2-chome, Kitaku, Osaka, 530-8323 JAPAN

PHONE : 81-6-6373-4349      FAX : 81-6-6373-4389