



TG-530

Technical Information

1. Performance Features

- Imparts excellent hydrostatic head pressure performance especially for cellulosic nonwovens
- Compatible with most textile additives
- Non-flammable

2. Typical Properties

Appearance.....	Off white emulsion
Ionic Characteristics.....	Cationic
pH.....	3~5
Specific gravity at 25°C (77°F).....	1.1
Analysis	19~21% Solids
	4~5% Tripropylene glycol
	74~76% Water
Solubility.....	Readily dissolves in cold water

3. Shipping & Storage

Non-Red Label (Non-flammable Material)

TG-530 should be stored at temperatures between 23 °F and 86 °F (-5°C and 30°C).

4. Safety / Toxicology

Before using this product, please read the current TG-530 Material Safety Data Sheet and the precautionary statement on the product package. Follow all applicable directions.

DAIKIN AMERICA, INC.

ADDRESS: 20 Olympic Drive, Orangeburg, New York 10962

EMERGENCY PHONE: 1-256-306-5000

PRODUCT INFORMATION: 1-800-365-9570

DAIKIN INDUSTRIES, LTD.

CHEMICAL DIVISION

ADDRESS: Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kitaku, Osaka, 530-8323 JAPAN

PHONE : 81-6-6373-4349 FAX : 81-6-6373-4389