



TG-533

Technical Information

1. Performance Features

- Imparts excellent hydrostatic head pressure performance for synthetic nonwoven fabrics.
- Compatible with most textile additives
- Non-flammable

2. Typical Properties

Appearance.....	Milky-white emulsion	
Ionic Characteristics.....	Nonionic	
pH.....	2~4	
Specific gravity at 25°C (77°F).....	1.09	
Analysis	20.0%	Solids
	5.4%	Tripropylene glycol
	74.6%	Water
Solubility.....	Readily dissolves in cold water	

3. Shipping & Storage

Non-Red Label (Non-flammable Material)

TG-533 should be stored at temperatures between 23 °F and 86 °F (-5°C and 30°C).

4. Safety / Toxicology

Before using this product, please read the current TG-533 Material Safety Data Sheet and the precautionary statement on the product package. Follow all applicable directions.

DAIKIN AMERICA, INC.

ADDRESS: 20 Olympic Drive, Orangeburg, New York 10962

EMERGENCY PHONE: 1-256-306-5000

PRODUCT INFORMATION: 1-800-365-9570

DAIKIN INDUSTRIES, LTD.

CHEMICAL DIVISION

ADDRESS: Umeda Center Bldg.,4-12, Nakazaki-Nishi 2-chome, Kitaku, Osaka, 530-8323 JAPAN

PHONE : 81-6-6373-4349 FAX : 81-6-6373-4389