



TG-580

Durable water and oil repellent for textiles Technical information

1. Performance Features

- TG-580 imparts excellent durable water and oil repellency to nearly all type of fabrics.
- TG-580 imparts excellent water and oil repellency to fabrics.
- TG-580 is compatible with other textile finishing additives.
- TG-580 is non-flammable.
- TG-580 is APEO (polyoxyethylene alkylphenol adduct) free.

2. Typical properties

Appearance	Off white or pale yellow emulsion	
Ionic characteristics	Nonionic	
pH	3.0~8.0	
Specific gravity at 25°C (77°F)	Approx. 1.12	
Analysis	30%	Solids
	7 - 8%	Tripropylene glycol
	61 - 63%	Water
Solubility	Readily dissolves in cold water	

3. Shipping & Storage

Non-Red Label (Non-flammable Material)

TG-580 should be stored at temperatures between 23°F and 86°F(-5°C and 30°C).

4. Safety/Toxicology

Before using this product, please read the current TG-580 Material Safety Data Sheet and the precautionary statement on the product package. Follow all applicable directions.

DAIKIN AMERICA, INC.

ADDRESS: 20 Olympic Drive, Orangeburg, New York 10962

EMERGENCY PHONE: 1-256-306-5000

PRODUCT INFORMATION: 1-800-365-9570

DAIKIN INDUSTRIES, LTD.

CHEMICAL DIVISION

ADDRESS: Umeda Center Bldg.,4-12, Nakazaki-Nishi 2-chome, Kitaku, Osaka, 530-8323 JAPAN

PHONE : 81-6-6373-4349 FAX : 81-6-6373-4389